

→ 4850 D AUTOMATIC CUTTER WITH DIGITAL DISPLAY

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | electric blade and clamp drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | automatic clamp is guided on both sides to apply even pressure along entire cutting width (can be lowered or raised independently from blade) | dual side guides on front and rear tables | spindle-guided back gauge with calibrated crank, narrow separations, and plastic gliders | digital display for precise back gauge positioning | bright, LED optical cutting line | all-metal construction | stand with storage shelf

Dimensions (D x W x H): $38 \frac{1}{4}$ x $29 \frac{3}{4}$ x $48 \frac{1}{2}$ inches, Shipping weight: 556 lbs.



DIGITAL DISPLAY



A digital measurement readout ensures exact positioning of back gauge.

DEAD SAFETY COVE



The transparent rear safety cover gives a clear view of side guides and back gauge.

AUTOMATIC CLAMP CONTROL



The automatic clamp control allows clamp to be moved up or down, independent of blade.

→ TRIUMPH 4850 D

Cutting width	18 1/8"
Cutting height	3"
Narrow cut	1 1/4"
Cutting length behind blade	17 11/16
Table length	13 %"

in front of blade

Motor 2 hp

Power supply 115 V, 60 Hz*

* 20 amp dedicated line required

Dealer:







1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com