


→ 352F PROFESSIONAL SERIES TABLETOP FOLDER

dual roller friction feed system accepts a wide variety of stocks, including carbonless sheets | adjusts in seconds for standard and custom folds | variable speed control | powered exit conveyor | sheet separation from top of fanned stack | polyurethane foam rollers eliminate the need for fold roller pressure settings | heavy-duty, non-flexing side frames | needle bearings for high speed production | optional extended delivery system, crossfold for right-angle folding, and slitting, scoring, and perforating attachments

Dimensions (D x W x H): 22 1/4 x 41 3/4 x 14 1/2 inches, Shipping weight: 105 lbs.



DUAL FEED ROLLERS



The dual roller feed system folds a wide range of stock.

POWERED CONVEYOR



A powered exit conveyor ensures smooth ejection of folded paper.

→ 352F

| | |
|----------------|---------------------------------|
| Speed | 22,000 sheets/hr* |
| Paper size | 2" x 2 1/4" to 14" x 21 1/4" |
| Paper weight | 13 to 110 lbs.* |
| Sheet capacity | 300* |
| Power supply | 115 V, 60 Hz |

* may vary due to variations in paper and power supply

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com